

CTD data collected during MOCNESS tows to Georges Bank and the Gulf of Maine on the US GLOBEC Georges Bank Broadscale and Process cruises, 1994-1999

Website: <https://www.bco-dmo.org/dataset/2302>

Data Type: Cruise Results

Version: 1

Version Date: 2005-10-27

Project

» [U.S. GLOBEC Georges Bank](#) (GB)

Program

» [U.S. GLOBal ocean ECosystems dynamics](#) (U.S. GLOBEC)

Contributors	Affiliation	Role
Bollens, Steve M.	Washington State University	Principal Investigator
Bucklin, Ann	University of New Hampshire (UNH/OPAL)	Principal Investigator
Garrahan, Peter	University of Rhode Island (URI-GSO)	Principal Investigator
Gifford, Dian J.	University of Rhode Island (URI-GSO)	Principal Investigator
Green, John	National Marine Fisheries Service (NMFS)	Principal Investigator
Lough, Greg	National Marine Fisheries Service (NMFS)	Principal Investigator
Miller, Charles B.	Oregon State University (OSU)	Principal Investigator
Sibunka, John	National Oceanic and Atmospheric Administration (NOAA)	Principal Investigator
Taylor, Maureen	National Marine Fisheries Service (NMFS)	Principal Investigator
Wiebe, Peter H.	Woods Hole Oceanographic Institution (WHOI)	Principal Investigator
Allison, Dicky	Woods Hole Oceanographic Institution (WHOI)	BCO-DMO Data Manager

Abstract

The MOCNESS is based on the Tucker Trawl principle (Tucker, 1951). The particular MOCNESS system from which these CTD data came is one of three net systems. The MOCNESS-10 (with 10 m² nets) carries 6 nets of 3.0-mm circular mesh which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe et al., 1976). In all three systems, "the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer." (Wiebe et al., 1985) In addition, data were collected from four other sensors attached to the frame: the Transmissometer, the Fluorometer, the Downwelling light sensor, and the Oxygen sensor. A SeaBird underwater pump was also included in the sensor suite.

Table of Contents

- [Coverage](#)
- [Dataset Description](#)
 - [Methods & Sampling](#)
- [Data Files](#)
- [Parameters](#)
- [Instruments](#)

- [Deployments](#)
- [Project Information](#)
- [Program Information](#)
- [Funding](#)

Coverage

Spatial Extent: N:76.1552 E:113.3667 S:0.0333 W:-138.9962

Temporal Extent: 1994-05-17 - 1999-06-24

Dataset Description

The MOCNESS is based on the Tucker Trawl principle (Tucker, 1951). The particular MOCNESS system from which these CTD data came is one of three net systems. The MOCNESS-10 (with 10 m² nets) carries 6 nets of 3.0-mm circular mesh which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe *et al.*, 1976). In all three systems, "the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer." (Wiebe *et al.*, 1985) In addition, data were collected from four other sensors attached to the frame: the Transmissometer, the Fluorometer, the Downwelling light sensor, and the Oxygen sensor. A SeaBird underwater pump was also included in the sensor suite.

It should be noted that whenever the data are of questionable value, "50.000" is written in the particular data field.

The following notes are cruise-specific:

OC319: Lats and Lons for first two tows are missing because gps string not yet available.

Unless otherwise indicated, these data have not been post-processed.

For additional information, contact the [chief scientist](#) for the cruise or the [U.S. GLOBEC Data Management Office](#) (DMO).

Note: Some variables have been eliminated from the display but are nevertheless available. These variables include: oxycurrent, oxytemp, tempco, and echo.

References

Fofonoff and Millard, 1983, UNESCO technical papers in Marine Sciences, #44 Tucker, G.H., 1951. Relation of fishes and other organisms to the scattering of underwater sound. *Journal of Marine Research*, **10**: 215-238. Wiebe, P.H., K.H. Burt, S. H. Boyd, A.W. Morton, 1976. The multiple opening/closing net and environmental sensing system for sampling zooplankton. *Journal of Marine Research*, **34(3)**: 313-326 Wiebe, P.H., A.W. Morton, A.M. Bradley, R.H. Backus, J.E. Craddock, V. Barber, T.J. Cowles and G.R. Flierl, 1985. New developments in the MOCNESS, an apparatus for sampling zooplankton and micronekton. *Marine Biology*, **87**: 313-323.
updated October 27 2005, gfh

Methods & Sampling

The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow

count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.

[[table of contents](#) | [back to top](#)]

Data Files

File
ctd_mocness.csv (Comma Separated Values (.csv), 204.42 MB) MD5:9ce278dc60c3799af06e4ffee727614a Primary data file for dataset ID 2302

[[table of contents](#) | [back to top](#)]

Parameters

Parameter	Description	Units
cruiseid	Cruise identification, e.g. EN261, for Endeavor cr. 261	
year	Four digit year, local time	
brief_desc	Brief cruise description, such as: broad-scale, process, mooring, etc.,	
tow	Tow number	
day_local	Day of month, local time, 1 - 31	
month_local	Month of year, local time 1 - 12	
station	station number, from event log	
station_std	standard station number, from eventlog	
yday_local	year day, Julian Calendar local time	decimal day
time_local	time of day; local time using 24 hour clock.	HHmm.m
press	depth of sample	meters
temp	temperature	degrees C.
potemp	potential temperature ¹	degrees C.
sal	salinity calculated from conductivity; if salinity exceeds 50 or is less than 0 o/oo, salinity is set to 50.	
sigma_0	potential density ¹ at the surface	kg/m ³ -1000
flvolt	fluorescence (0-5 volts)	volts
angle	angle of net frame relative to vertical (0-89 degrees)	
flow	consecutive flow counts	
hzvel	horizontal net velocity m/min	meters/minute
vtvel	vertical net velocity m/min	meters/minute
vol_net	volume filtered	meters ³
trans_v	light transmission (0-5 volts)	volts
net	sequential MOCNESS net number	
lat	latitude, negative = South	decimal degrees
lon	longitude, negative = West	decimal degrees
datatype	MOCNESS size	

[[table of contents](#) | [back to top](#)]

Instruments

Dataset-specific Instrument Name	MOCNESS.25
Generic Instrument Name	MOCNESS.25
Dataset-specific Description	The MOCNESS-.25 carries nine rectangular nets (1/4-m ²), usually with 64 micrometer mesh.
Generic Instrument Description	The Multiple Opening/Closing Net and Environmental Sensing System or MOCNESS is a family of net systems based on the Tucker Trawl principle. The MOCNESS-1/4 carries nine 1/4-m ² nets usually of 64 micrometer mesh and is used to sample the larger micro-zooplankton.

Dataset-specific Instrument Name	MOCNESS1
Generic Instrument Name	MOCNESS1
Dataset-specific Description	The MOCNESS-1 has nine rectangular nets (1m x 1.4 m) which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe et al., 1976).
Generic Instrument Description	The Multiple Opening/Closing Net and Environmental Sensing System or MOCNESS is a family of net systems based on the Tucker Trawl principle. The MOCNESS-1 carries nine 1-m ² nets usually of 335 micrometer mesh and is intended for use with the macrozooplankton. All nets are black to reduce contrast with the background. A motor/toggle release assembly is mounted on the top portion of the frame and stainless steel cables with swaged fittings are used to attach the net bar to the toggle release. A stepping motor in a pressure compensated case filled with oil turns the escapement crankshaft of the toggle release which sequentially releases the nets to an open then closed position on command from the surface. -- from the MOCNESS Operations Manual (1999 + 2003).

Dataset-specific Instrument Name	MOCNESS10
Generic Instrument Name	MOCNESS10
Dataset-specific Description	The MOCNESS-10 (with 10 m ² nets) carries 6 nets of 3.0-mm circular mesh.
Generic Instrument Description	The Multiple Opening/Closing Net and Environmental Sensing System (MOCNESS) is based on the Tucker Trawl principle (Tucker, 1951). The MOCNESS-10 (with 10 m ² nets) carries 6 nets of 3.0-mm circular mesh which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe et al., 1976). In this system, "the underwater unit sends a data frame, comprising temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds" (Wiebe et al., 1985).

[[table of contents](#) | [back to top](#)]

Deployments

AL9403II

Website	https://www.bco-dmo.org/deployment/57368
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9403.2/AL9403.2.pdf
Start Date	1994-05-17
End Date	1994-05-28
Description	<p>process</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9508

Website	https://www.bco-dmo.org/deployment/57373
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9508/a9508rp2.HTM
Start Date	1995-07-10
End Date	1995-07-20
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9605

Website	https://www.bco-dmo.org/deployment/57375
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9605/al9605.html
Start Date	1996-05-06
End Date	1996-05-17
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9701

Website	https://www.bco-dmo.org/deployment/57378
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9701/cral9701.htm
Start Date	1997-01-13
End Date	1997-01-20
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9707

Website	https://www.bco-dmo.org/deployment/57380
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9707/al9707.html
Start Date	1997-06-18
End Date	1997-06-28
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9801

Website	https://www.bco-dmo.org/deployment/57382
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9801/al9801.html
Start Date	1998-01-07
End Date	1998-01-19
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9806

Website	https://www.bco-dmo.org/deployment/57384
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9806/al9806.html
Start Date	1998-05-13
End Date	1998-05-22
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9808

Website	https://www.bco-dmo.org/deployment/57385
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9808/al9808.html
Start Date	1998-06-16
End Date	1998-06-26
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9901

Website	https://www.bco-dmo.org/deployment/57386
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9901/al9901.html
Start Date	1999-01-12
End Date	1999-01-24
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

AL9906

Website	https://www.bco-dmo.org/deployment/57388
Platform	R/V Albatross IV
Report	http://globec.whoi.edu/globec-dir/reports/al9906/al9906rpt.html
Start Date	1999-06-14
End Date	1999-06-24
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN261

Website	https://www.bco-dmo.org/deployment/57401
Platform	R/V Endeavor
Start Date	1995-02-10
End Date	1995-02-20
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN263

Website	https://www.bco-dmo.org/deployment/57403
Platform	R/V Endeavor
Report	http://globec.whoi.edu/globec-dir/reports/en263/EN263.pdf
Start Date	1995-03-13
End Date	1995-03-24
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN265

Website	https://www.bco-dmo.org/deployment/57405
Platform	R/V Endeavor
Start Date	1995-04-11
End Date	1995-04-22
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN268

Website	https://www.bco-dmo.org/deployment/57409
Platform	R/V Endeavor
Start Date	1995-06-26
End Date	1995-07-06
Description	<p>process</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN276

Website	https://www.bco-dmo.org/deployment/57413
Platform	R/V Endeavor
Report	http://globec.who.edu/globec-dir/reports/en276/EN276.pdf
Start Date	1996-01-10
End Date	1996-01-22
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN278

Website	https://www.bco-dmo.org/deployment/57414
Platform	R/V Endeavor
Start Date	1996-02-13
End Date	1996-02-25
Description	<p>broad-scale</p> <p>Methods & Sampling</p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN282

Website	https://www.bco-dmo.org/deployment/57415
Platform	R/V Endeavor
Start Date	1996-04-08
End Date	1996-04-20
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN320

Website	https://www.bco-dmo.org/deployment/57427
Platform	R/V Endeavor
Report	http://globec.whoi.edu/globec-dir/reports/en320new/en320mda.htm
Start Date	1999-03-10
End Date	1999-03-23
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

EN325

Website	https://www.bco-dmo.org/deployment/57432
Platform	R/V Endeavor
Start Date	1999-06-13
End Date	1999-06-30
Description	<p>process</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

OC300

Website	https://www.bco-dmo.org/deployment/57446
Platform	R/V Oceanus
Report	http://globec.whoi.edu/globec-dir/reports/oc300/oc300rpt.mr7.html
Start Date	1997-03-16
End Date	1997-03-28
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

OC302

Website	https://www.bco-dmo.org/deployment/57448
Platform	R/V Oceanus
Report	http://globec.whoi.edu/globec-dir/reports/oc302/oce302.html
Start Date	1997-04-22
End Date	1997-05-02
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

OC319

Website	https://www.bco-dmo.org/deployment/57452
Platform	R/V Oceanus
Report	http://globec.whoi.edu/globec-dir/reports/oc319/oc319new/oc319rpt.8april98.htm
Start Date	1998-03-15
End Date	1998-03-27
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

OC336

Website	https://www.bco-dmo.org/deployment/57459
Platform	R/V Oceanus
Report	http://globec.whoi.edu/globec-dir/reports/oc336/oc336cruise-report.html
Start Date	1999-02-11
End Date	1999-02-23
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

OC341

Website	https://www.bco-dmo.org/deployment/57464
Platform	R/V Oceanus
Report	http://globec.whoi.edu/globec-dir/reports/oc341/reptoc341.html
Start Date	1999-04-16
End Date	1999-04-27
Description	<p>broad-scale</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

SJ9503

Website	https://www.bco-dmo.org/deployment/57482
Platform	R/V Seward Johnson
Start Date	1995-03-14
End Date	1995-03-24
Description	<p>process larvae</p> <p>Methods & Sampling The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

SJ9505

Website	https://www.bco-dmo.org/deployment/57484
Platform	R/V Seward Johnson
Report	http://globec.whoi.edu/globec-dir/reports/sj9505/sj9505.html
Start Date	1995-04-07
End Date	1995-04-21
Description	<p>Process cruise looking for cod and haddock larvae.</p> <p>Methods & Sampling the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

SJ9507

Website	https://www.bco-dmo.org/deployment/57486
Platform	R/V Seward Johnson
Report	http://globec.who.edu/globec-dir/reports/sj9507/SJ9507.pdf
Start Date	1995-05-08
End Date	1995-05-26
Description	<p>process larvae</p> <p>Methods & Sampling the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

[[table of contents](#) | [back to top](#)]

Project Information

U.S. GLOBEC Georges Bank (GB)

Website: http://globec.who.edu/globec_program.html

Coverage: Georges Bank, Gulf of Maine, Northwest Atlantic Ocean

The U.S. GLOBEC [Georges Bank](#) Program is a large multi- disciplinary multi-year oceanographic effort. The proximate goal is to understand the population dynamics of key species on the Bank - Cod, [Haddock](#), and two species of zooplankton ([Calanus finmarchicus](#) and [Pseudocalanus](#)) - in terms of their coupling to the physical environment and in terms of their [predators and prey](#). The ultimate goal is to be able to predict changes in the distribution and abundance of these species as a result of changes in their physical and biotic environment as well as to anticipate how their populations might respond to climate change.

The effort is substantial, requiring broad-scale surveys of the entire Bank, and process studies which focus both on the links between the target species and their physical environment, and the determination of fundamental aspects of these species' life history (birth rates, growth rates, death rates, etc).

Equally important are the modelling efforts that are ongoing which seek to provide realistic predictions of the flow field and which utilize the life history information to produce an integrated view of the dynamics of the populations.

The U.S. GLOBEC Georges Bank [Executive Committee \(EXCO\)](#) provides program leadership and effective communication with the funding agencies.

[[table of contents](#) | [back to top](#)]

Program Information

U.S. GLOBal ocean ECosystems dynamics (U.S. GLOBEC)

Website: <http://www.usglobec.org/>

Coverage: Global

U.S. GLOBEC (GLOBal ocean ECosystems dynamics) is a research program organized by oceanographers and fisheries scientists to address the question of how global climate change may affect the abundance and production of animals in the sea.

The U.S. GLOBEC Program currently had major research efforts underway in the Georges Bank / Northwest Atlantic Region, and the Northeast Pacific (with components in the California Current and in the Coastal Gulf of Alaska). U.S. GLOBEC was a major contributor to International GLOBEC efforts in the Southern Ocean and Western Antarctic Peninsula (WAP).

[[table of contents](#) | [back to top](#)]

Funding

Funding Source	Award
National Science Foundation (NSF)	unknown GB NSF
National Oceanic and Atmospheric Administration (NOAA)	unknown GB NOAA

[[table of contents](#) | [back to top](#)]