

# CTD data collected during MOCNESS hauls in the Georges Bank from 1993-1999 on the R/V Albatross IV, R/V Endeavor, R/V Oceanus, R/V Seward Johnson (GB project)

Website: <https://www.bco-dmo.org/dataset/2511>

Version: 2005-10-27

## Project

» [U.S. GLOBEC Georges Bank](#) (GB)

## Program

» [U.S. GLOBal ocean ECosystems dynamics](#) (U.S. GLOBEC)

Contributors	Affiliation	Role
<a href="#">Bollens, Steve M.</a>	Washington State University	Principal Investigator
<a href="#">Bucklin, Ann</a>	University of New Hampshire (UNH/OPAL)	Principal Investigator
<a href="#">Durbin, Edward</a>	University of Rhode Island (URI-GSO)	Principal Investigator
<a href="#">Garrahan, Peter</a>	University of Rhode Island (URI-GSO)	Principal Investigator
<a href="#">Gibson, James</a>	University of Rhode Island (URI-GSO)	Principal Investigator
<a href="#">Gifford, Dian J.</a>	University of Rhode Island (URI-GSO)	Principal Investigator
<a href="#">Green, John</a>	National Marine Fisheries Service (NMFS)	Principal Investigator
<a href="#">Greene, Charles H</a>	Cornell University (Cornell)	Principal Investigator
<a href="#">Irish, Jim</a>	Woods Hole Oceanographic Institution (WHOI)	Principal Investigator
<a href="#">Lough, Greg</a>	National Marine Fisheries Service (NMFS)	Principal Investigator
<a href="#">Manning, James P.</a>	Northeast Fisheries Science Center - Woods Hole (NOAA NEFSC)	Principal Investigator
<a href="#">Miller, Charles B.</a>	Oregon State University (OSU)	Principal Investigator
<a href="#">Mountain, David</a>	National Marine Fisheries Service (NMFS)	Principal Investigator
<a href="#">Sibunka, John</a>	National Oceanic and Atmospheric Administration (NOAA)	Principal Investigator
<a href="#">Taylor, Maureen</a>	National Marine Fisheries Service (NMFS)	Principal Investigator
<a href="#">Wiebe, Peter H.</a>	Woods Hole Oceanographic Institution (WHOI)	Principal Investigator
<a href="#">Allison, Dicky</a>	Woods Hole Oceanographic Institution (WHOI)	BCO-DMO Data Manager

## Table of Contents

- [Dataset Description](#)
  - [Methods & Sampling](#)
- [Data Files](#)
- [Parameters](#)
- [Instruments](#)
- [Deployments](#)
- [Project Information](#)
- [Program Information](#)
- [Funding](#)

## Dataset Description

The MOCNESS is based on the Tucker Trawl principle (Tucker, 1951). The particular MOCNESS system from which these CTD data came is one of three net systems. The MOCNESS-1 has nine rectangular nets (1m x 1.4 m) which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe *et al.*, 1976). In all three systems, the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds. Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used. Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg. Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer. (Wiebe *et al.*, 1985) In addition, data were collected from four other sensors attached to the frame: the Transmissometer, the Fluorometer, the Downwelling light sensor, and the Oxygen sensor. A SeaBird underwater pump was also included in the sensor suite.

**It should be noted that whenever the data are of questionable value, 50.000 is written in the particular data field.**

Unless otherwise indicated, these data have not been post-processed.

For additional information, contact the [chief scientist](#) for the cruise or the [U.S. GLOBEC Data Management Office](#) (DMO).

**Note:** Some variables have been eliminated from the display but are nevertheless available. These variables include: oxycurrent, oxytemp, tempco, and echo.

## References

Fofonoff and Millard, 1983, UNESCO technical papers in Marine Sciences, #44  
Tucker, G.H., 1951. Relation of fishes and other organisms to the scattering of underwater sound. *Journal of Marine Research*, **10**: 215-238.  
Wiebe, P.H., K.H. Burt, S. H. Boyd, A.W. Morton, 1976. The multiple opening/closing net and environmental sensing system for sampling zooplankton. *Journal of Marine Research*, **34(3)**: 313-326  
Wiebe, P.H., A.W. Morton, A.M. Bradley, R.H. Backus, J.E. Craddock, V. Barber, T.J. Cowles and G.R. Flierl, 1985. New developments in the MOCNESS, an apparatus for sampling zooplankton and micronekton. *Marine Biology*, **87**: 313-323.  
*updated October 27 2005, gfh*

## Methods & Sampling

The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.

[ [table of contents](#) | [back to top](#) ]

---

## Data Files

<b>File</b>
<b>ctd_mocness.csv</b> (Comma Separated Values (.csv), 154.87 MB) MD5:482efc96350533cd3516516cca826860
Primary data file for dataset ID 2511

[ [table of contents](#) | [back to top](#) ]

## Parameters

Parameter	Description	Units
cruiseid	cruise identification, e.g. NBP0202, for RVIB Palmer cruise 0202	
temp	temperature of water	degrees C
datatype	sampling method - instrument type, e.g. MOCNESS-1 or MOCNESS-10	
year	year	
brief_desc	brief cruise description, such as process or mooring	
tow	tow number	
day_local	day of month, GMT, 1-31	
month_local	month of year, GMT, 1 - 12	
station	station number, from event log	
station_std	standard station number, from event log	
yrday_local	year day as a decimal, based on Julian calendar, GMT	YYY.Y
time_local	time, GMT using 24 hour clock to decimal minutes	HHmm.m
press	depth of observation or sample	meters
potemp	potential temperature or theta1 <sup>1</sup> Fofonoff and Millard, 1983, UNESCO technical papers in Marine Sciences, #44	
sal	salinity calculated from conductivity, bad values are set to 50	
sigma_0	potential density1 <sup>1</sup> Fofonoff and Millard, 1983, UNESCO technical papers in Marine Sciences, #44	
flvolt	relative fluorescence (0-5 volts)	volts
angle	angle of net frame relative to vertical (0-89 degrees)	degrees
flow	consecutive flow counts	
hzvel	horizontal net velocity	m/min
vtvel	vertical net velocity	m/min
vol_net	volume filtered	meters <sup>3</sup>
trans_v	transmissometry or light transmission, (0-5 volts)	volts
O2	dissolved oxygen	ml/liter
lite	downwelling light	volts
net	MOCNESS net number, (00-08)	
lat	latitude, negative = South	DD.D
lon	longitude, negative = West	DDD.D

[ [table of contents](#) | [back to top](#) ]

## Instruments

<b>Dataset-specific Instrument Name</b>	CTD MOCNESS
<b>Generic Instrument Name</b>	CTD MOCNESS
<b>Dataset-specific Description</b>	<p>The MOCNESS-1 has nine rectangular nets (1m x 1.4 m) which are opened and closed sequentially by commands through conducting cable from the surface (Wiebe et al., 1976). In all three systems, "the underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds. Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used. Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg. Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer." (Wiebe et al., 1985) In addition, data were collected from four other sensors attached to the frame: the Transmissometer, the Fluorometer, the Downwelling light sensor, and the Oxygen sensor. A SeaBird underwater pump was also included in the sensor suite.</p>
<b>Generic Instrument Description</b>	<p>The CTD part of the MOCNESS includes 1) a pressure (depth) sensor which is a thermally isolated titanium strain gauge with a standard range of 0-5000 decibars full scale, 2) A Sea Bird temperature sensor whose frequency output is measured and sent to the surface for logging and conversion to temperature by the software in the MOCNESS computer (The system allows better than 1 milli-degree resolution at 10 Hz sampling rate), and 3) A Sea Bird conductivity sensor whose output frequency is measured and sent to the surface for logging and conversion to conductivity by the software in the computer (The system allows better than 1 micro mho/cm at 10 Hz sampling rate). The data rate depends on the speed of the computer and the quality of the cable. With a good cable, the system can operate at 2400 baud, sampling all variables at 2 times per second. One sample every 4 seconds is the default, although the hardware can operate much faster. (From The MOCNESS Manual)</p>

[ [table of contents](#) | [back to top](#) ]

---

## Deployments

AL9306

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57366">https://www.bco-dmo.org/deployment/57366</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9306/AL9306DataReport.pdf">http://globec.whoi.edu/globec-dir/reports/al9306/AL9306DataReport.pdf</a>
<b>Start Date</b>	1993-05-18
<b>End Date</b>	1993-05-29
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9403II

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57368">https://www.bco-dmo.org/deployment/57368</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9403.2/AL9403.2.pdf">http://globec.whoi.edu/globec-dir/reports/al9403.2/AL9403.2.pdf</a>
<b>Start Date</b>	1994-05-17
<b>End Date</b>	1994-05-28
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9404

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57369">https://www.bco-dmo.org/deployment/57369</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9404/AL9404.htm">http://globec.whoi.edu/globec-dir/reports/al9404/AL9404.htm</a>
<b>Start Date</b>	1994-05-31
<b>End Date</b>	1994-06-10
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9505

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57371">https://www.bco-dmo.org/deployment/57371</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9505/al9505rot.pdf">http://globec.whoi.edu/globec-dir/reports/al9505/al9505rot.pdf</a>
<b>Start Date</b>	1995-05-09
<b>End Date</b>	1995-05-18
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9506

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57372">https://www.bco-dmo.org/deployment/57372</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9506/al9506new.html">http://globec.whoi.edu/globec-dir/reports/al9506/al9506new.html</a>
<b>Start Date</b>	1995-06-05
<b>End Date</b>	1995-06-15
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9508

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57373">https://www.bco-dmo.org/deployment/57373</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9508/a9508rp2.HTM">http://globec.whoi.edu/globec-dir/reports/al9508/a9508rp2.HTM</a>
<b>Start Date</b>	1995-07-10
<b>End Date</b>	1995-07-20
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9513

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57374">https://www.bco-dmo.org/deployment/57374</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9513/AL9513.pdf">http://globec.whoi.edu/globec-dir/reports/al9513/AL9513.pdf</a>
<b>Start Date</b>	1995-10-30
<b>End Date</b>	1995-11-08
<b>Description</b>	<p>long term mooring deployment</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9605

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57375">https://www.bco-dmo.org/deployment/57375</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9605/al9605.html">http://globec.whoi.edu/globec-dir/reports/al9605/al9605.html</a>
<b>Start Date</b>	1996-05-06
<b>End Date</b>	1996-05-17
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9607



<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57376">https://www.bco-dmo.org/deployment/57376</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9607/AL9607.pdf">http://globec.whoi.edu/globec-dir/reports/al9607/AL9607.pdf</a>
<b>Start Date</b>	1996-06-03
<b>End Date</b>	1996-06-13
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9612

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57377">https://www.bco-dmo.org/deployment/57377</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9612/al9612c.html">http://globec.whoi.edu/globec-dir/reports/al9612/al9612c.html</a>
<b>Start Date</b>	1996-11-04
<b>End Date</b>	1996-11-08
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9701

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57378">https://www.bco-dmo.org/deployment/57378</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9701/cra19701.htm">http://globec.whoi.edu/globec-dir/reports/al9701/cra19701.htm</a>
<b>Start Date</b>	1997-01-13
<b>End Date</b>	1997-01-20
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9707

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57380">https://www.bco-dmo.org/deployment/57380</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9707/al9707.html">http://globec.whoi.edu/globec-dir/reports/al9707/al9707.html</a>
<b>Start Date</b>	1997-06-18
<b>End Date</b>	1997-06-28
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9801

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57382">https://www.bco-dmo.org/deployment/57382</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9801/al9801.html">http://globec.whoi.edu/globec-dir/reports/al9801/al9801.html</a>
<b>Start Date</b>	1998-01-07
<b>End Date</b>	1998-01-19
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9806

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57384">https://www.bco-dmo.org/deployment/57384</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9806/al9806.html">http://globec.whoi.edu/globec-dir/reports/al9806/al9806.html</a>
<b>Start Date</b>	1998-05-13
<b>End Date</b>	1998-05-22
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9808

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57385">https://www.bco-dmo.org/deployment/57385</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9808/al9808.html">http://globec.whoi.edu/globec-dir/reports/al9808/al9808.html</a>
<b>Start Date</b>	1998-06-16
<b>End Date</b>	1998-06-26
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9901

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57386">https://www.bco-dmo.org/deployment/57386</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9901/al9901.html">http://globec.whoi.edu/globec-dir/reports/al9901/al9901.html</a>
<b>Start Date</b>	1999-01-12
<b>End Date</b>	1999-01-24
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b></p> <p>The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9904

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57387">https://www.bco-dmo.org/deployment/57387</a>
<b>Platform</b>	R/V Albatross IV
<b>Start Date</b>	1999-05-19
<b>End Date</b>	1999-05-27
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### AL9906

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57388">https://www.bco-dmo.org/deployment/57388</a>
<b>Platform</b>	R/V Albatross IV
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/al9906/al9906rpt.html">http://globec.whoi.edu/globec-dir/reports/al9906/al9906rpt.html</a>
<b>Start Date</b>	1999-06-14
<b>End Date</b>	1999-06-24
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN261

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57401">https://www.bco-dmo.org/deployment/57401</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1995-02-10
<b>End Date</b>	1995-02-20
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN263

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57403">https://www.bco-dmo.org/deployment/57403</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en263/EN263.pdf">http://globec.whoi.edu/globec-dir/reports/en263/EN263.pdf</a>
<b>Start Date</b>	1995-03-13
<b>End Date</b>	1995-03-24
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN265

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57405">https://www.bco-dmo.org/deployment/57405</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1995-04-11
<b>End Date</b>	1995-04-22
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN268

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57409">https://www.bco-dmo.org/deployment/57409</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1995-06-26
<b>End Date</b>	1995-07-06
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN274

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57412">https://www.bco-dmo.org/deployment/57412</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en274/EN274.pdf">http://globec.whoi.edu/globec-dir/reports/en274/EN274.pdf</a>
<b>Start Date</b>	1995-09-29
<b>End Date</b>	1995-10-05
<b>Description</b>	<p>long term mooring recovery</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN276

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57413">https://www.bco-dmo.org/deployment/57413</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en276/EN276.pdf">http://globec.whoi.edu/globec-dir/reports/en276/EN276.pdf</a>
<b>Start Date</b>	1996-01-10
<b>End Date</b>	1996-01-22
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN278



<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57414">https://www.bco-dmo.org/deployment/57414</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1996-02-13
<b>End Date</b>	1996-02-25
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN282

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57415">https://www.bco-dmo.org/deployment/57415</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1996-04-08
<b>End Date</b>	1996-04-20
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN296

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57419">https://www.bco-dmo.org/deployment/57419</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en296/EN296.pdf">http://globec.whoi.edu/globec-dir/reports/en296/EN296.pdf</a>
<b>Start Date</b>	1997-03-04
<b>End Date</b>	1997-03-16
<b>Description</b>	<p>process zooplankton vital rates</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer. During this cruise, the latitude and longitude information from the satellite feed were not connected to the MOCNESS acquisition system. Consequently, position information information is not available for this data set.</p>

#### EN307

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57424">https://www.bco-dmo.org/deployment/57424</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en307/greenrpt.html">http://globec.whoi.edu/globec-dir/reports/en307/greenrpt.html</a>
<b>Start Date</b>	1997-10-08
<b>End Date</b>	1997-10-17
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### EN319

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57426">https://www.bco-dmo.org/deployment/57426</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en319/en319rept.html">http://globec.whoi.edu/globec-dir/reports/en319/en319rept.html</a>
<b>Start Date</b>	1999-02-21
<b>End Date</b>	1999-03-04
<b>Description</b>	<p>process zooplankton vital rates</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN320

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57427">https://www.bco-dmo.org/deployment/57427</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en320new/en320mda.htm">http://globec.whoi.edu/globec-dir/reports/en320new/en320mda.htm</a>
<b>Start Date</b>	1999-03-10
<b>End Date</b>	1999-03-23
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN321

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57428">https://www.bco-dmo.org/deployment/57428</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1999-03-28
<b>End Date</b>	1999-04-11
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN322

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57429">https://www.bco-dmo.org/deployment/57429</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1999-04-17
<b>End Date</b>	1999-05-02
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN325

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57432">https://www.bco-dmo.org/deployment/57432</a>
<b>Platform</b>	R/V Endeavor
<b>Start Date</b>	1999-06-13
<b>End Date</b>	1999-06-30
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN330

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57433">https://www.bco-dmo.org/deployment/57433</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en330/en330new.htm">http://globec.whoi.edu/globec-dir/reports/en330/en330new.htm</a>
<b>Start Date</b>	1999-10-16
<b>End Date</b>	1999-10-26
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### EN331

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57434">https://www.bco-dmo.org/deployment/57434</a>
<b>Platform</b>	R/V Endeavor
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/en331/en331rpt.6sept2000.html">http://globec.whoi.edu/globec-dir/reports/en331/en331rpt.6sept2000.html</a>
<b>Start Date</b>	1999-12-04
<b>End Date</b>	1999-12-13
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC300

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57446">https://www.bco-dmo.org/deployment/57446</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc300/oc300rpt.mr7.html">http://globec.whoi.edu/globec-dir/reports/oc300/oc300rpt.mr7.html</a>
<b>Start Date</b>	1997-03-16
<b>End Date</b>	1997-03-28
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC301

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57447">https://www.bco-dmo.org/deployment/57447</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc301/oc301.html">http://globec.whoi.edu/globec-dir/reports/oc301/oc301.html</a>
<b>Start Date</b>	1997-04-05
<b>End Date</b>	1997-04-17
<b>Description</b>	<p>process fish vital rates</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC302

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57448">https://www.bco-dmo.org/deployment/57448</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc302/oc302.html">http://globec.whoi.edu/globec-dir/reports/oc302/oc302.html</a>
<b>Start Date</b>	1997-04-22
<b>End Date</b>	1997-05-02
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC303

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57449">https://www.bco-dmo.org/deployment/57449</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc303/oc303.html">http://globec.whoi.edu/globec-dir/reports/oc303/oc303.html</a>
<b>Start Date</b>	1997-05-06
<b>End Date</b>	1997-05-23
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC319

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57452">https://www.bco-dmo.org/deployment/57452</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc319/oc319new/oc319rpt.8april98.htm">http://globec.whoi.edu/globec-dir/reports/oc319/oc319new/oc319rpt.8april98.htm</a>
<b>Start Date</b>	1998-03-15
<b>End Date</b>	1998-03-27
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC332



<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57456">https://www.bco-dmo.org/deployment/57456</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc332/oc332rpt.html">http://globec.whoi.edu/globec-dir/reports/oc332/oc332rpt.html</a>
<b>Start Date</b>	1998-10-19
<b>End Date</b>	1998-10-30
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### OC334

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57458">https://www.bco-dmo.org/deployment/57458</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc334/cruise-report.html">http://globec.whoi.edu/globec-dir/reports/oc334/cruise-report.html</a>
<b>Start Date</b>	1998-12-03
<b>End Date</b>	1998-12-13
<b>Description</b>	<p>process</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

#### OC336

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57459">https://www.bco-dmo.org/deployment/57459</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc336/oc336cruise-report.html">http://globec.whoi.edu/globec-dir/reports/oc336/oc336cruise-report.html</a>
<b>Start Date</b>	1999-02-11
<b>End Date</b>	1999-02-23
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### OC341

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57464">https://www.bco-dmo.org/deployment/57464</a>
<b>Platform</b>	R/V Oceanus
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/oc341/reptoc341.html">http://globec.whoi.edu/globec-dir/reports/oc341/reptoc341.html</a>
<b>Start Date</b>	1999-04-16
<b>End Date</b>	1999-04-27
<b>Description</b>	<p>broad-scale</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### SJ9503

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57482">https://www.bco-dmo.org/deployment/57482</a>
<b>Platform</b>	R/V Seward Johnson
<b>Start Date</b>	1995-03-14
<b>End Date</b>	1995-03-24
<b>Description</b>	<p>process larvae</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### SJ9505

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57484">https://www.bco-dmo.org/deployment/57484</a>
<b>Platform</b>	R/V Seward Johnson
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/sj9505/sj9505.html">http://globec.whoi.edu/globec-dir/reports/sj9505/sj9505.html</a>
<b>Start Date</b>	1995-04-07
<b>End Date</b>	1995-04-21
<b>Description</b>	<p>Process cruise looking for cod and haddock larvae.</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

### SJ9507

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/57486">https://www.bco-dmo.org/deployment/57486</a>
<b>Platform</b>	R/V Seward Johnson
<b>Report</b>	<a href="http://globec.whoi.edu/globec-dir/reports/sj9507/SJ9507.pdf">http://globec.whoi.edu/globec-dir/reports/sj9507/SJ9507.pdf</a>
<b>Start Date</b>	1995-05-08
<b>End Date</b>	1995-05-26
<b>Description</b>	<p>process larvae</p> <p><b>Methods &amp; Sampling</b>  The underwater unit sends a data frame, comprised of temperature, depth, conductivity, net-frame angle, flow count, time, number of open net, and net opening/closing, to the deck unit in a compressed hexadecimal format every 2 seconds and from the deck unit to a microcomputer every 4 seconds... Temperature (to approximately 0.01 deg C) and conductivity are measured with SEABIRD sensors. Normally, a modified T.S.K.-flowmeter is used... Both the temperature and conductivity sensors and the flowmeter are mounted on top of the frame so that they face horizontally when the frame is at a towing angle of 45deg... Calculations of salinity (to approximately 0.01 o/oo S), potential temperature (theta), potential density (sigma), the oblique and vertical velocities of the net, and the approximate volume filtered by each net are made after each string of data has been received by the computer.</p>

[ [table of contents](#) | [back to top](#) ]

---

## Project Information

### U.S. GLOBEC Georges Bank (GB)

**Website:** [http://globec.whoi.edu/globec\\_program.html](http://globec.whoi.edu/globec_program.html)

**Coverage:** Georges Bank, Gulf of Maine, Northwest Atlantic Ocean

The U.S. GLOBEC [Georges Bank](#) Program is a large multi- disciplinary multi-year oceanographic effort. The proximate goal is to understand the population dynamics of key species on the Bank - Cod, [Haddock](#), and two species of zooplankton ([Calanus finmarchicus](#) and [Pseudocalanus](#)) - in terms of their coupling to the physical environment and in terms of their [predators and prey](#). The ultimate goal is to be able to predict changes in the distribution and abundance of these species as a result of changes in their physical and biotic environment as well as to anticipate how their populations might respond to climate change.

The effort is substantial, requiring broad-scale surveys of the entire Bank, and process studies which focus both on the links between the target species and their physical environment, and the determination of fundamental aspects of these species' life history (birth rates, growth rates, death rates, etc).

Equally important are the modelling efforts that are ongoing which seek to provide realistic predictions of the flow field and which utilize the life history information to produce an integrated view of the dynamics of the populations.

The U.S. GLOBEC Georges Bank [Executive Committee \(EXCO\)](#) provides program leadership and effective communication with the funding agencies.

[ [table of contents](#) | [back to top](#) ]

---

## Program Information

### U.S. GLOBAL ocean ECosystems dynamics (U.S. GLOBEC)

**Website:** <http://www.usglobec.org/>

**Coverage:** Global

U.S. GLOBEC (GLOBAL ocean ECosystems dynamics) is a research program organized by oceanographers and fisheries scientists to address the question of how global climate change may affect the abundance and production of animals in the sea.

The U.S. GLOBEC Program currently had major research efforts underway in the Georges Bank / Northwest Atlantic Region, and the Northeast Pacific (with components in the California Current and in the Coastal Gulf of Alaska). U.S. GLOBEC was a major contributor to International GLOBEC efforts in the Southern Ocean and Western Antarctic Peninsula (WAP).

[ [table of contents](#) | [back to top](#) ]

---

## Funding

Funding Source	Award
National Science Foundation (NSF)	<a href="#">unknown GB NSF</a>
National Oceanic and Atmospheric Administration (NOAA)	<a href="#">unknown GB NOAA</a>

[ [table of contents](#) | [back to top](#) ]