

Sediment geochemical and microbial activity data collected on R/V Oden along the East Siberian Arctic Shelf from 2014 (ESAS Water Column Methane project)

Website: <https://www.bco-dmo.org/dataset/660527>

Data Type: Cruise Results

Version: 1

Version Date: 2016-10-04

Project

» [The East Siberian Arctic Shelf as a Source of Atmospheric Methane: First Approach to Quantitative Assessment](#) (ESAS Water Column Methane)

Contributors	Affiliation	Role
Joye, Samantha B.	University of Georgia (UGA)	Principal Investigator, Contact
Samarkin, Vladimir	University of Georgia (UGA)	Co-Principal Investigator
Ake, Hannah	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager

Abstract

Sediment geochemical and microbial activity data collected on R/V Oden along the East Siberian Arctic Shelf from 2014 (ESAS Water Column Methane project)

Table of Contents

- [Coverage](#)
- [Dataset Description](#)
 - [Methods & Sampling](#)
 - [Data Processing Description](#)
- [Data Files](#)
- [Related Publications](#)
- [Parameters](#)
- [Instruments](#)
- [Deployments](#)
- [Project Information](#)
- [Funding](#)

Coverage

Spatial Extent: N:78.942 E:172.361 S:74.44 W:125.243

Temporal Extent: 2014 - 2014

Dataset Description

These data describe sediment geochemical and microbial activity from the Lappet Sea, East Siberian Arctic Shelf.

All of the methods used to determine concentrations and calculate rates of activity are given in the following papers: Joye S.B. et al. 2010; Joye, S. B. et al. 2010 and Orcutt, B. N. et al. 2005.

Methods & Sampling

Acquisition methods are described in the following publication: Orcutt, B.N. et al. 2005

Core sectioning, porewater collection and analysis

At each sampling site, sediment sub-samples were collected for porewater analyses and at selected depths for microbial rate assays (AOM, anaerobic oxidation of methane oxidation; methanogenesis (MOG) from bicarbonate and acetate). Sediment was expelled from core liner using a hydraulic extruder under anoxic conditions. The depth intervals for extrusion varied. At each depth interval, a sub-sample was collected into a cut-off syringe for dissolved methane concentration quantification. Another 5 mL sub-sample was collected into pre-weighed and pre-combusted glass vial for determination of porosity (determined by the change in weight after drying at 80 degrees celsius to a constant weight). The remaining material was used for porewater extraction. Sample fixation and analyses for dissolved constituents followed the methods of Joye et al. (2010).

Microbial Activity Measurements

To determine AOM and MOG rates, 8 to 12 sub-samples (5 cm³) were collected from a core by manual insertion of a glass tube. For AOM, 100 uL of dissolved ¹⁴CH₄ tracer (about 2,000,000 DPM as gas) was injected into each core. Samples were incubated for 36 to 48 hours at in situ temperature. Following incubation, samples were transferred to 20 mL glass vials containing 2 mL of 2M NaOH (which served to arrest biological activity and fix ¹⁴CO₂ as ¹⁴C-HCO₃⁻). Each vial was sealed with a teflon-lined screw cap, vortexed to mix the sample and base, and immediately frozen. Time zero samples were fixed immediately after radiotracer injection. The specific activity of the tracer substrate (¹⁴CH₄) was determined by injecting 50 uL directly into scintillation cocktail (Scintiverse BD) followed by liquid scintillation counting. The accumulation of ¹⁴C product (¹⁴CO₂) was determined by acid digestion following the method of Joye et al. (2010). The AOM rate was calculated using equation 1:

$$\text{AOM Rate} = [\text{CH}_4] \times \alpha_{\text{CH}_4} / t \times (a\text{-}^{14}\text{CO}_2 / a\text{-}^{14}\text{CH}_4) \quad (\text{Eq. 1})$$

Here, the AOM Rate is expressed as nmol CH₄ oxidized per cm³ sediment per day (nmol cm⁻³ d⁻¹), [CH₄] is the methane concentration (uM), α_{CH_4} is the isotope fractionation factor for AOM (1.06; (ALPERIN and REEBURGH, 1988)), t is the incubation time (d), a-¹⁴CO₂ is the activity of the product pool, and a-¹⁴CH₄ is the activity of the substrate pool. If methane concentration was not available, the turnover time of the ¹⁴CH₄ tracer is presented.

Rates of bicarbonate-based-methanogenesis and acetoclastic methanogenesis were determined by incubating samples in gas-tight, closed-tube vessels without headspace, to prevent the loss of gaseous ¹⁴CH₄ product during sample manipulation. These sample tubes were sealed using custom-designed plungers (black Hungate stoppers with the lip removed containing a plastic "tail" that was run through the stopper) were inserted at the base of the tube; the sediment was then pushed via the plunger to the top of the tube until a small amount protruded through the tube opening. A butyl rubber septa was then eased into the tube opening to displace sediment in contact with the atmosphere and close the tube, which was then sealed with an open-top screw cap. The rubber materials used in these assays were boiled in 1N NaOH for 1 hour, followed by several rinses in boiling milliQ, to leach potentially toxic substances.

A volume of radiotracer solution (100 uL of ¹⁴C-HCO₃⁻ tracer (~1 x 10⁷ dpm in slightly alkaline milliQ water) or 1,2-¹⁴C-CH₃COO⁻ tracer (~5 x 10⁷ dpm in slightly alkaline milliQ water)) was injected into each sample. Samples were incubated as described above and then 2 ml of 2N NaOH was injected through the top stopper into each sample to terminate biological activity (time zero samples were fixed prior to tracer injection). Samples were mixed to evenly distribute NaOH through the sample. Production of ¹⁴CH₄ was quantified by stripping methane from the tubes with an air carrier, converting the ¹⁴CH₄ to ¹⁴CO₂ in a combustion furnace, and subsequent trapping of the ¹⁴CO₂ in NaOH as carbonate (CRAGG et al., 1990; CRILL and MARTENS, 1986). Activity of ¹⁴CO₂ was measured subsequently by liquid scintillation counting.

The rates of Bi-MOG and Ac-MOG rates were calculated using equations 2 and 3, respectively:

$$\text{Bi-MOG Rate} = [\text{HCO}_3^-] \times \alpha_{\text{HCO}_3^-} / t \times (a\text{-}^{14}\text{CH}_4 / a\text{-H}^{14}\text{CO}_3^-) \quad (\text{Eq. 2})$$

$$\text{Ac-MOG Rate} = [\text{CH}_3\text{COO}^-] \times \alpha_{\text{CH}_3\text{COO}^-} / t \times (a\text{-}^{14}\text{CH}_4 / a\text{-}^{14}\text{CH}_3^{14}\text{COO}^-) \quad (\text{Eq. 3})$$

Both rates are expressed as nmol HCO₃⁻ or CH₃COO⁻, respectively, reduced cm⁻³ d⁻¹, $\alpha_{\text{HCO}_3^-}$ and $\alpha_{\text{CH}_3\text{COO}^-}$ are the isotope fractionation factors for MOG (assumed to be 1.06). [HCO₃⁻] and [CH₃COO⁻] are the pore water bicarbonate (mM) and acetate (uM) concentrations, respectively, t is incubation time (d), a-¹⁴CH₄ is the activity of the product pool, and a-H¹⁴CO₃⁻ and a-¹⁴CH₃¹⁴COO⁻ are the activities of the substrate pools. If samples for substrate concentration determination were not available, the substrate turnover constant instead of the rate is presented.

For water column methane oxidation rate assays, triplicate 20 mL of live water (in addition to one 20 mL sample which was killed with ethanol (750 uL of pure EtOH) before tracer addition) were transferred from the

CTD into serum vials. Samples were amended with 2×10^6 DPM of ^3H -labeled-methane tracer and incubated for 24 to 72 hours (linearity of activity was tested and confirmed). After incubation, samples were fixed with ethanol, as above, and a sub-sample to determine total sample activity (^3H -methane + ^3H -water) was collected. Next, the sample was purged with nitrogen to remove the ^3H -methane tracer and a sub-sample was amended with scintillation fluid and counted on a shipboard scintillation counter to determine the activity of tracer in the product of ^3H -methane oxidation, ^3H -water. The methane oxidation rate was calculated as:

$$\text{MOX Rate} = [\text{methane concentration in nM}] \times \alpha_{\text{CH}_4/t} \times (a\text{-}^3\text{H}\text{-H}_2\text{O}/a\text{-}^3\text{H}\text{-CH}_4\text{-}) \quad (\text{Eq. 3})$$

Data Processing Description

BCO-DMO Data Processing Notes:

- filled in blank cells with "nd"
- separated month and year into two columns
- converted lat/lons to decimal degrees
- replaced the code "MUC" with it's complete definition "multiple core"
- replaced the code "BDL" with it's complete definition "below defined level"

[[table of contents](#) | [back to top](#)]

Data Files

File
arctic_sediment.csv (Comma Separated Values (.csv), 7.60 KB) MD5:9de93e894a75fef2876068c9933d8104
Primary data file for dataset ID 660527

[[table of contents](#) | [back to top](#)]

Related Publications

Joye, S. B., Bowles, M. W., Samarkin, V. A., Hunter, K. S., & Niemann, H. (2010). Biogeochemical signatures and microbial activity of different cold-seep habitats along the Gulf of Mexico deep slope. *Deep Sea Research Part II: Topical Studies in Oceanography*, 57(21-23), 1990–2001. doi:[10.1016/j.dsr2.2010.06.001](https://doi.org/10.1016/j.dsr2.2010.06.001)
Methods

Joye, S. B., MacDonald, I. R., Leifer, I., & Asper, V. (2011). Magnitude and oxidation potential of hydrocarbon gases released from the BP oil well blowout. *Nature Geoscience*, 4(3), 160–164. doi:[10.1038/ngeo1067](https://doi.org/10.1038/ngeo1067)
Methods

Orcutt, B., Boetius, A., Elvert, M., Samarkin, V., & Joye, S. B. (2005). Molecular biogeochemistry of sulfate reduction, methanogenesis and the anaerobic oxidation of methane at Gulf of Mexico cold seeps. *Geochimica et Cosmochimica Acta*, 69(17), 4267–4281. doi:[10.1016/j.gca.2005.04.012](https://doi.org/10.1016/j.gca.2005.04.012)
Methods

[[table of contents](#) | [back to top](#)]

Parameters

Parameter	Description	Units
station	Station where sampling occurred	unitless
collection_type	Method used to collect samples	unitless
year	Year of sampling; YYYY	unitless
month	Month of sampling; mm	unitless
lat	Latitude	decimal degrees
lon	Longitude	decimal degrees
sediment_depth	Depth of sediment; negative depth values represent overlying water samples	centimeters
sample_ID	PI issued sample ID number	unitless
sed_CH4	Methane concentration in sediment	microns (uM)
AOM_rate	Anaerobic Oxidation of Methane; CH4 oxidized in sediment per day; Rates were measured at stations 13 and 23 only.	picomole per centimeter per day (pmol/cm/day)
turnover_14_CH3COO_MOG	14-CH3COO methanogenesis turnover; Rates were measured at stations 13 and 23 only.	percent
turnover_H14_CO3_MOG	H14-CO3 methanogenesis turnover; Rates were measured at stations 13 and 23 only.	percent
turnover_SRR	Sulfate reduction methanogenesis turnover; Rates were measured at stations 13 and 23 only.	percent

[[table of contents](#) | [back to top](#)]

Instruments

Dataset-specific Instrument Name	CTD
Generic Instrument Name	CTD - profiler
Dataset-specific Description	Used to collect water column samples
Generic Instrument Description	The Conductivity, Temperature, Depth (CTD) unit is an integrated instrument package designed to measure the conductivity, temperature, and pressure (depth) of the water column. The instrument is lowered via cable through the water column. It permits scientists to observe the physical properties in real-time via a conducting cable, which is typically connected to a CTD to a deck unit and computer on a ship. The CTD is often configured with additional optional sensors including fluorometers, transmissometers and/or radiometers. It is often combined with a Rosette of water sampling bottles (e.g. Niskin, GO-FLO) for collecting discrete water samples during the cast. This term applies to profiling CTDs. For fixed CTDs, see https://www.bco-dmo.org/instrument/869934 .

Dataset-specific Instrument Name	Liquid scintillation counter
Generic Instrument Name	Liquid Scintillation Counter
Dataset-specific Description	Used to determine activity of tracer substrate
Generic Instrument Description	Liquid scintillation counting is an analytical technique which is defined by the incorporation of the radiolabeled analyte into uniform distribution with a liquid chemical medium capable of converting the kinetic energy of nuclear emissions into light energy. Although the liquid scintillation counter is a sophisticated laboratory counting system used to quantify the activity of particulate emitting (β and α) radioactive samples, it can also detect the auger electrons emitted from ^{51}Cr and ^{125}I samples.

Dataset-specific Instrument Name	Multiple core
Generic Instrument Name	Multi Corer
Dataset-specific Description	Core used in sampling
Generic Instrument Description	The Multi Corer is a benthic coring device used to collect multiple, simultaneous, undisturbed sediment/water samples from the seafloor. Multiple coring tubes with varying sampling capacity depending on tube dimensions are mounted in a frame designed to sample the deep ocean seafloor. For more information, see Barnett et al. (1984) in <i>Oceanologica Acta</i> , 7, pp. 399-408.

[[table of contents](#) | [back to top](#)]

Deployments

SWERUS-C3

Website	https://www.bco-dmo.org/deployment/660539
Platform	R/V Oden
Report	http://www.swerus-c3.geo.su.se/index.php/expedition
Start Date	2014-07-01

[[table of contents](#) | [back to top](#)]

Project Information

The East Siberian Arctic Shelf as a Source of Atmospheric Methane: First Approach to Quantitative Assessment (ESAS Water Column Methane)

Coverage: East Siberian Arctic Shelf

We propose to study methane (CH_4) release over the East Siberian Arctic shelf (ESAS), the largest (~10% of

the world ocean shelf area) and the shallowest shelf (mean depth <50 m) of the world ocean. Until recently, the ESAS was not considered a CH₄ source due to subsea permafrost's impermeability, which completely isolated it from modern biogeochemical cycles. The ESAS stores the world's largest hydrocarbon stocks, mostly as shallow Arctic hydrates, and thus represents an enormous potential CH₄ atmospheric source that could result from global warming-triggered permafrost degradation. Increased CH₄ fluxes could occur as numerous weak seeps or strong bubble plumes over large areas. Due to the shallow nature of the ESAS, the majority of ESAS CH₄ likely avoids oxidation and escapes to the atmosphere. To assess whether sudden, large-scale CH₄ release occurs or is likely to occur in the future, we will investigate the migration pathway characteristics and identify the controlling factors of CH₄ flux from the seabed, in the water column, and to the atmosphere.

Our central hypothesis is that seabed CH₄ fluxes are significant year-round sources while atmospheric fluxes are only significant during ice-free periods. To understand both the temporal and spatial variability of CH₄ fluxes, we will test the sub-hypotheses that ESAS emissions are strongly modulated by seasonal factors including water-column mixing and ice cover, while seabed CH₄ emissions are much more weakly modulated (or not at all), and that the spatial distribution of emission correlates with the location of shallow and deep-water fault zones, and submerged thermokarst areas - primary geologic rather than biologic control. We will: 1) distinguish different CH₄ sources 2) quantify the importance of microbial production and consumption of CH₄ including seasonal variations vs. release of previously originated CH₄ from seabed reservoirs; 3) evaluate contributions of different components (spatial, seasonal and transport components) to the annual CH₄ flux; 4) investigate controlling factors and model CH₄ release during critical periods such as storms, fall convection and ice-break up period and over critical area such as fault zones and thermokarst-affected areas; 5) use modeling to extend results to the entire ESAS and for climate change scenarios.

Water column hydrography and geochemical measurements will be conducted during a summer cruise and a winter expedition. To distinguish between individual CH₄ sources we will measure stable carbon isotope ratios ($\delta^{13}C_{CH_4}$, $\delta^{13}C_{DIC}$, $\delta^{13}C_{POC}$), D/H ratio of CH₄ and water (δD_{CH_4} , δD_{H_2O}), CH₄ radiocarbon age ($\Delta^{14}C$), and the abundance of non-CH₄ hydrocarbons in water, air and sediment samples. To elucidate importance of microbial production (methanogenesis) we will estimate in situ production in particles; CH₄ consumption (oxidation) will be measured in the water column and at the ice-water interface. To evaluate total flux, we will perform direct flux measurements (4 helicopter surveys) using eddy-correlation techniques to obtain integrative rates of CH₄ flux and assess strength of the current CH₄ source over two area. To assess contribution of ebullition, we will measure seafloor direct bubble flux over 6 control and 2 test sites on a nested range of sonar scales (3.5 kHz, largest), to multibeam sonar scanner (decameter), to turbine tents (meter), and a combination of bubble video imaging and bubble modeling (vent scale). To evaluate factors controlling CH₄ fluxes, we will perform investigations of seabed permeability for gases using geophysics and ³He/⁴He ratio. Modeling will aim to develop a regional flux model.

[[table of contents](#) | [back to top](#)]

Funding

Funding Source	Award
NSF Division of Polar Programs (NSF PLR)	PLR-1023444

[[table of contents](#) | [back to top](#)]