

# Abundance of taxa from images collected by the ROV/SCINI along benthic transects under the McMurdo Ice Shelf, Nov./Dec. 2008

**Website:** <https://www.bco-dmo.org/dataset/744702>

**Data Type:** Other Field Results

**Version:** 1

**Version Date:** 2018-08-28

## Project

» [Development of a Remotely Operated Vehicle for Under Sea Ice Research in Polar Environments](#) (SCINI)

Contributors	Affiliation	Role
<a href="#">Kim, Stacy</a>	Moss Landing Marine Laboratories (MLML)	Principal Investigator
<a href="#">Copley, Nancy</a>	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager

## Abstract

This dataset includes abundances of taxa that were observed in images taken along benthic transects under the McMurdo Ice Shelf, Antarctica during November and December 2008. The imagery was collected with a Remotely Operated Vehicle called the 'Submersible Capable of under Ice Navigation and Imaging' (ROV/SCINI). Transects ranged in area from 3 to 33 meters<sup>2</sup>.

## Table of Contents

- [Coverage](#)
- [Dataset Description](#)
  - [Methods & Sampling](#)
  - [Data Processing Description](#)
- [Data Files](#)
- [Parameters](#)
- [Instruments](#)
- [Deployments](#)
- [Project Information](#)
- [Funding](#)

## Coverage

**Spatial Extent:** N:-78.2167 E:164.2433 S:-78.2233 W:164.225

**Temporal Extent:** 2008-11-25 - 2008-12-06

## Dataset Description

This dataset includes abundances of taxa that were observed in images taken along benthic transects under the McMurdo Ice Shelf, Antarctica during November and December 2008. The imagery was collected with a Remotely Operated Vehicle called the 'Submersible Capable of under Ice Navigation and Imaging' (ROV/SCINI). Transects ranged in area from 3 to 33 meters<sup>2</sup>.

## Methods & Sampling

Sites are centered at 78° 13.2'S, 164° 14.1'E, from North 500 meters north of this location, and South 500 meters south of this location, within the center of the barranca.

Animal densities are reported as number per square meter. Transect imagery was collected with the ROV SCINI. Organisms were identified to the lowest possible taxon.

## Data Processing Description

BCO-DMO Processing:

- transposed columns to rows
- added conventional header with dataset name, PI name, version date
- modified parameter names to conform with BCO-DMO naming conventions
- converted latitude and longitude to decimal degrees
- phylum and taxonomic name were combined to form one term

[ [table of contents](#) | [back to top](#) ]

---

## Data Files

File
<b>MIS_Benthic_Transect.csv</b> (Comma Separated Values (.csv), 99.19 KB) MD5:9cd58a80b6b82abd4f2d529ab612384a Primary data file for dataset ID 744702

[ [table of contents](#) | [back to top](#) ]

---

## Parameters

Parameter	Description	Units
lat	latitude; north is positive	decimal degrees
lon	longitude; east is positive	decimal degrees
dive	ROV SCINI deployment identifier	unitless
replicate	replicate number	unitless
transect_area_m2	transect area	meters ^2
taxon	Operational Taxonomic Unit (OUT) identified to lowest possible taxon	unitless
abundance_m2	Abundance of the taxon found along the transect	number per square meter

[ [table of contents](#) | [back to top](#) ]

---

## Instruments

<b>Dataset-specific Instrument Name</b>	ROV/SCINI
<b>Generic Instrument Name</b>	Remotely Operated Vehicle
<b>Dataset-specific Description</b>	Submersible Capable of under Ice Navigation and Imaging (SCINI) is a small, slender vehicle that can fit through a 20 cm hole in the ice, allowing for deployment without heavy drilling equipment and with minimal logistical support. Its maximum depth capability is 300 m. SCINI is equipped with two video cameras, scaling lasers, and lights, with forward speeds of up to 4 knots. SCINI uses Ethernet over power on a 400 m long two-wire tether. A long baseline acoustic positioning system is used for navigation which uses a combination of two to four acoustic transducers hanging below the ice and a synchronized pinger on the vehicle for positional accuracy of better than 1 meter. [See Cazenave, F, R Zook, D Carroll, M Flagg, S Kim. 2011. Development of the ROV SCINI and deployment in McMurdo Sound, Antarctica. Journal of Ocean Technology 6(3):39-58.]
<b>Generic Instrument Description</b>	Remotely operated underwater vehicles (ROVs) are unoccupied, highly maneuverable underwater robots operated by a person aboard a surface vessel. They are linked to the ship by a group of cables that carry electrical signals back and forth between the operator and the vehicle. Most are equipped with at least a video camera and lights. Additional equipment is commonly added to expand the vehicle's capabilities. These may include a still camera, a manipulator or cutting arm, water samplers, and instruments that measure water clarity, light penetration, and temperature.

[ [table of contents](#) | [back to top](#) ]

## Deployments

### McMurdo SCINI 2008

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/745442">https://www.bco-dmo.org/deployment/745442</a>
<b>Platform</b>	McMurdo Station
<b>Start Date</b>	2008-12-02
<b>End Date</b>	2008-12-06
<b>Description</b>	The ROV 'Submersible Capable of under Ice Navigation and Imaging' (SCINI) was deployed on the McMurdo Ice Shelf to collect images of under-ice fauna.

[ [table of contents](#) | [back to top](#) ]

## Project Information

### Development of a Remotely Operated Vehicle for Under Sea Ice Research in Polar Environments (SCINI)

**Coverage:** McMurdo Sound, McMurdo Ice Shelf

#### *NSF Award Abstract:*

In marine habitats worldwide, the zone between scuba-diving depths (to 40 m) and surge-free depths (below 200 m) has been poorly studied. Under ice-covered seas, wave motion is minimal to nonexistent, and the zone between 40 and 200 m is accessible to ROVs. Polar marine research has the benefit of stable sea ice platforms for staging and deploying instruments like ROVs, but this requires a hole that is, for most ROVs, a meter in diameter. This proposal develops an ROV that can be deployed through a 15 cm hole that can be drilled with a

hand-held power head, requiring minimal logistical support and technical expertise. The new ROV provides access to regions that remain unstudied, expanding our scientific reach and ability to address new questions. We will develop, test, and modify the ROV while accomplishing several overlapping and interdependent science objectives, including (1) exploration and documentation of rates and patterns of ecological succession from one of the most extreme coastal habitats in the world, (2) a survey of two unique benthic habitats and communities beyond scuba diving depths (at 40-170 m), which are almost completely unknown to most researchers and assembly of individual photographs into high-resolution images of the seafloor and (3) testing of protocols for conducting sonar mapping and creating high resolution continuous bathymetric maps of the entire seafloor around McMurdo Station. The ROV will be constructed as modules; this allows flexibility to change the ROV capabilities to suit different missions. Some components can be purchased off the shelf (e.g. VideoRay high resolution and low light video cameras), but may require development of some custom integration software. Power is provided from the surface via a 2 conductor tether; bi-directional high speed data is modulated on the tether as well, providing 84 mbs of data and unlimited dive duration. The topside controls consist of a laptop computer and joystick for the pilot. Many of the control functions and display screens could be accessed via the Internet for educational demonstrations and interactions. Two graduate students will participate fully in the project. Several other Antarctic scientists have indicated a strong interest in utilizing this tool in their research and it will be available to a pool of users on completion of the project.

[ [table of contents](#) | [back to top](#) ]

---

## Funding

Funding Source	Award
<a href="#">NSF Office of Polar Programs (formerly NSF PLR) (NSF OPP)</a>	<a href="#">PLR-0619622</a>

[ [table of contents](#) | [back to top](#) ]