

# Domoic acid assimilation in copepods from experiments conducted using water samples collected in northern Gulf of Mexico in 2019

**Website:** <https://www.bco-dmo.org/dataset/808402>

**Data Type:** experimental

**Version:** 1

**Version Date:** 2020-06-24

## Project

» [The biotic and abiotic controls on the Silicon cycle in the northern Gulf of Mexico](#) (CLASIC)

Contributors	Affiliation	Role
<a href="#">Krause, Jeffrey W.</a>	Dauphin Island Sea Lab (DISL)	Principal Investigator
<a href="#">Maiti, Kanchan</a>	Louisiana State University (LSU)	Co-Principal Investigator
<a href="#">Marquez Jr., Israel A.</a>	Dauphin Island Sea Lab (DISL)	Contact
<a href="#">York, Amber D.</a>	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager

## Abstract

Domoic acid assimilation in copepods by consuming organic polymers containing domoic acid. Results from lab experiments designed to investigate the role of organic polymers in trophic transfer of domoic acid, using *Acartia tonsa* as a model organism. Water samples were collected in the northern Gulf of Mexico in 2019.

## Table of Contents

- [Coverage](#)
- [Dataset Description](#)
  - [Methods & Sampling](#)
  - [Data Processing Description](#)
- [Data Files](#)
- [Related Publications](#)
- [Parameters](#)
- [Instruments](#)
- [Project Information](#)
- [Funding](#)

## Coverage

**Spatial Extent:** Lat:30.278166 Lon:-87.554261

**Temporal Extent:** 2019-02-07

## Dataset Description

Domoic acid assimilation in copepods by consuming organic polymers containing domoic acid. Results from lab experiments designed to investigate the role of organic polymers in trophic transfer of domoic acid, using *Acartia tonsa* as a model organism. Water samples were collected in the northern Gulf of Mexico in 2019.

Related datasets:

Organic polymers and domoic acid <https://www.bco-dmo.org/dataset/808280>

Field domoic acid and copepods <https://www.bco-dmo.org/dataset/808413>

## Methods & Sampling

## Location

Water collection sites in the northern Gulf of Mexico, particularly at the mouth of Mobile Bay and Little Lagoon, AL.

## Water Collection

Briefly, water was collected from the field using a 5-gallon bucket, pre-screened with a 200  $\mu\text{m}$  nitex mesh, and gently poured into 10-20 L carboys and kept in the dark until returning to the laboratory for same-day processing.

## Terminology

dDA – dissolved Domoic Acid

pDAa – particulate Domoic Acid (algal fraction)

pDAOP – particulate Domoic Acid (bound to organic polymers)

cDA – Domoic Acid in copepods

POC – Particulate Organic Carbon

## Organic polymer formation and sorption of DA

Seawater organic polymers were formed in controlled laboratory conditions to verify whether they could scavenge dDA (see dataset <https://www.bco-dmo.org/dataset/808280>). Surface seawater was collected from Dauphin Island (AL, USA) and filtered through a new 0.2  $\mu\text{m}$  polycap filter (Pall Brand, USA). The freshly filtered seawater was partitioned into 1-L polycarbonate bottles and the initial measurements of dDA, pDA, cDA, pDAOP, and POC were made. POC was used as a proxy for organic polymer formation. The same filtration techniques were used for dDA and pDA as described above. Laboratory-reared adult *Acartia tonsa* were collected on a 200  $\mu\text{m}$  screen and gently rinsed with freshly filtered artificial seawater, then transferred into 2 mL cryovials and stored in  $-20^{\circ}\text{C}$  until analyzed for cDA. Twenty-five mm glass fiber filters were pre-combusted at  $500^{\circ}\text{C}$  for four hours and used to collect organic polymers. The organic polymer collection method was modified from Passow et al. (1995); loss of organic polymers via filtration was minimized by maintaining low-vacuum ( $<200$  mbar) and filtering samples for a maximum of 15 minutes. Lastly, the treatment bottles were spiked with a DA standard to bring the final concentration to 10  $\mu\text{g}$  DA L $^{-1}$  and, for specific treatment bottles, 30 copepods were added to each bottle. Bottles were then placed on orbital shaker tables and gently shaken for 24 hours. Controls were not shaken. Samples for dDA, pDA, cDA, pDAOP, and POC were collected after the 24-hour time period.

## Liquid chromatography-mass spectrometry method for domoic acid quantification

LC-MS sample preparation followed was modified from Wang et al. (2012) for the determination of dDA, pDA, pDAOP and cDA. The samples for DA determination were cleaned and concentrated using Bond Elut LRC - C18, 200 mg, solid-phase extraction (SPE) columns from Agilent Technologies. For dDA, 30 mL seawater samples were filtered using a 47 mm glass fiber filter; the filtrate was collected and acidified with formic acid to yield a 0.2% final solution. SPE columns were conditioned with one column volume of HPLC-grade methanol followed by one column volume of HPLC-grade water. Samples were then loaded on the SPE column and filtered at  $\sim 1$  mL min $^{-1}$  using a vacuum manifold, followed by 10 mL of 0.2% formic acid as a rinse for the sample tube and SPE column. The SPE column was then allowed to go dry and was eluted with 1.5 mL of 20 mM ammonium acetate in 50% methanol (pH 8) and collected in a glass tube. The tubes were centrifuged for 5 minutes at  $\sim 1300 \times g$ , supernatant was transferred into an LC vial with a Pasteur pipette, and stored at  $4^{\circ}\text{C}$  until further analysis. For pDAa 100 mL of seawater were filtered through a 5  $\mu\text{m}$  polycarbonate filter and stored in a 50 mL polypropylene tube at  $-20^{\circ}\text{C}$ . Similarly, for pDAOP 150 mL of seawater was filtered through a pre-combusted 25 mm glass-fiber filter and stored at  $-20^{\circ}\text{C}$ . Prior to concentration and clean-up for pDA, pDAOP, and cDA, the filters were submerged in 2 mL of 80% methanol and sonicated to ensure cells and copepods were lysed. Sonication pulses were done for a total of 45 seconds (5 seconds on/off) on a Sonics Materials Ultrasonic Processor (model - VCX 130) at 75% power. Subsequent clean-up using the SPE column is the same as for the dDA samples.

An ultra-performance liquid chromatography (UPLC) – tandem mass spectrometry (MS) system was used for the quantification of DA. The LC-MS system consisted of Acquity UPLC system (Waters, Milford, MA) coupled to a 5500 QTRAP triple quadrupole / linear ion trap mass spectrometer equipped with a TurbolonSpray interface (Sciex, Foster City, CA, USA). The analytes were separated on a Luna C18 (2), 2.0  $\times$  100 mm column (Phenomenex, Torrance, CA, USA) with column temperature held at  $40^{\circ}\text{C}$ . The mobile phase was water (A) and 95% aqueous acetonitrile (B) with 0.1% formic acid additive and the flow rate was 0.4 mL/min. Gradient program was: 5% B for 3 min, linear gradient to 60% B at 10 min, 95% B at 10.1 min, hold at 95% B for 2 min.

MS was operated in positive ion mode. Ion spray voltage was 5 kV and declustering potential was 80 V. Gas parameter settings were: nebulizer gas, 50 psi; turbo gas, 50 psi at 500°C; curtain gas, 20 psi; and collision gas, medium setting. The collision energy applied was 25eV. The transitions used for selected reaction monitoring were m/z 312→266, 193, 220. The transition m/z 312→266 was used for quantitation.

For field-simulation experiment results and methodology see dataset <https://www.bco-dmo.org/dataset/808413>

## Data Processing Description

BCO-DMO Data Manager Processing Notes:

\* Data from sheet "Lab\_DA-copepods" from originally submitted Excel file "DATASET\_DA-org polymers-cop grazing\_BCO-DMO\_params\_IAM.xlsx" extracted to csv.

\* Column names modified to meet BCO-DMO naming conventions designed for interoperability (only letter, numbers, and underscores, no spaces).

[ [table of contents](#) | [back to top](#) ]

---

## Data Files

File
<b>lab-da-cope.csv</b> (Comma Separated Values (.csv), 831 bytes) MD5:6f69dba8c3a5e51913d7e47b4229b2f6 Primary data file for dataset ID 808402

[ [table of contents](#) | [back to top](#) ]

---

## Related Publications

Marquez, Israel A., Abraham, Ann, Krause, Jeffrey W. (in review) Marine snow consumption facilitates domoic acid entry into the marine food web without direct ingestion of Pseudo-nitzschia. Harmful Algae.

*Results*

Passow, U., & Alldredge, A. L. (1995). A dye-binding assay for the spectrophotometric measurement of transparent exopolymer particles (TEP). Limnology and Oceanography, 40(7), 1326-1335.

doi:[10.4319/l.1995.40.7.1326](https://doi.org/10.4319/l.1995.40.7.1326)

*Methods*

Wang, Z., Maucher-Fuquay, J., Fire, S. E., Mikulski, C. M., Haynes, B., Doucette, G. J., & Ramsdell, J. S. (2012). Optimization of solid-phase extraction and liquid chromatography-tandem mass spectrometry for the determination of domoic acid in seawater, phytoplankton, and mammalian fluids and tissues. Analytica Chimica Acta, 715, 71-79. doi:[10.1016/j.aca.2011.12.013](https://doi.org/10.1016/j.aca.2011.12.013)

*Methods*

[ [table of contents](#) | [back to top](#) ]

---

## Parameters

Parameter	Description	Units
ISO_DateTime.UTC	Date/Time (UTC) in ISO 8601 format yyyy-mm-ddTHH:MMZ	unitless
Latitude_N	Latitude in decimal degrees	decimal degrees
Longitude_W	Longitude in decimal degrees	decimal degrees
Date	Local date water was collected in format yyyymmdd	unitless
Time	Local time water was collected in format hhmm (24 hr)	unitless
Experiment	Experiment name	unitless
Treatment	Treatment name	unitless
Replicate_bottle	Letters denote a unique bottle that was sampled for each measurement	unitless
Num_copepods	Number of copepods per bottle	integer
cDA_mass	Total Domoic Acid in copepods	nanograms (ng)
cDA_indiv	Domoic Acid normalized per individual	picograms (pg) per copepod

[ [table of contents](#) | [back to top](#) ]

## Instruments

<b>Dataset-specific Instrument Name</b>	
<b>Generic Instrument Name</b>	Costech International Elemental Combustion System (ECS) 4010
<b>Generic Instrument Description</b>	The ECS 4010 Nitrogen / Protein Analyzer is an elemental combustion analyser for CHNSO elemental analysis and Nitrogen / Protein determination. The GC oven and separation column have a temperature range of 30-110 degC, with control of +/- 0.1 degC.

<b>Dataset-specific Instrument Name</b>	Sonics Materials Ultrasonic Processor (model - VCX 130)
<b>Generic Instrument Name</b>	Homogenizer
<b>Generic Instrument Description</b>	A homogenizer is a piece of laboratory equipment used for the homogenization of various types of material, such as tissue, plant, food, soil, and many others.

<b>Dataset-specific Instrument Name</b>	Acquity UPLC system coupled to a 5500 QTRAP
<b>Generic Instrument Name</b>	Mass Spectrometer
<b>Dataset-specific Description</b>	Acquity UPLC system (Waters, Milford, MA) coupled to a 5500 QTRAP triple quadrupole / linear ion trap mass spectrometer equipped with a TurbolonSpray interface (Sciex, Foster City, CA, USA).
<b>Generic Instrument Description</b>	General term for instruments used to measure the mass-to-charge ratio of ions; generally used to find the composition of a sample by generating a mass spectrum representing the masses of sample components.

[ [table of contents](#) | [back to top](#) ]

---

## Project Information

### The biotic and abiotic controls on the Silicon cycle in the northern Gulf of Mexico (CLASiC)

**Coverage:** Northern Gulf of Mexico, specifically the Louisiana Shelf region dominated by the discharge of the Mississippi River on the western side of the delta

#### *NSF Award Abstract:*

The Louisiana Shelf system in the northern Gulf of Mexico is fed by the Mississippi River and its many tributaries which contribute large quantities of nutrients from agricultural fertilizer to the region. Input of these nutrients, especially nitrogen, has led to eutrophication. Eutrophication is the process wherein a body of water such as the Louisiana Shelf becomes enriched in dissolved nutrients that increase phytoplankton growth which eventually leads to decreased oxygen levels in bottom waters. This has certainly been observed in this area, and diatoms, a phytoplankton which represents the base of the food chain, have shown variable silicon/nitrogen (Si/N) ratios. Because diatoms create their shells from silicon, their growth is controlled not only by nitrogen inputs but the availability of silicon. Lower Si/N ratios are showing that silicon may be playing an increasingly important role in regulating diatom production in the system. For this reason, a scientist from the University of South Alabama will determine the biogeochemical processes controlling changes in Si/N ratios in the Louisiana Shelf system. One graduate student on their way to a doctorate degree and three undergraduate students will be supported and trained as part of this project. Also, four scholarships for low-income, high school students from Title 1 schools will get to participate in a month-long summer Marine Science course at the Dauphin Island Sea Laboratory and be included in the research project. The study has significant societal benefits given this is an area where \$2.4 trillion gross domestic product revenue is tied up in coastal resources. Since diatoms are at the base of the food chain that is the biotic control on said coastal resources, the growth of diatoms in response to eutrophication is important to study.

Eutrophication of the Mississippi River and its tributaries has the potential to alter the biological landscape of the Louisiana Shelf system in the northern Gulf of Mexico by influencing the Si/N ratios below those that are optimal for diatom growth. A scientist from the University of South Alabama believes the observed changes in the Si/N ratio may indicate silicon now plays an important role in regulating diatom production in the system. As such, understanding the biotic and abiotic processes controlling the silicon cycle is crucial because diatoms dominate at the base of the food chain in this highly productive region. The study will focus on following issues: (1) the importance of recycled silicon sources on diatom production; (2) can heavily-silicified diatoms adapt to changing Si/N ratios more effectively than lightly-silicified diatoms; and (3) the role of reverse weathering in sequestering silicon thereby reducing diffusive pore-water transport. To attain these goals, a new analytical approach, the PDMPO method (compound 2-(4-pyridyl)-5-((4-(2-dimethylaminoethylamino-carbamoyl)methoxy)phenyl)oxazole) that quantitatively measures taxa-specific silica production would be used.

[ [table of contents](#) | [back to top](#) ]

---

## Funding

Funding Source	Award
<a href="#">NSF Division of Ocean Sciences (NSF OCE)</a>	<a href="#">OCE-1558957</a>
<a href="#">U.S. Food and Drug Administration (FDA)</a>	<a href="#">5U19FD005923-04</a>

[ [table of contents](#) | [back to top](#) ]