

Acoustic properties of sediments collected from the Northern Gulf of Mexico following laboratory resuspension at the Dauphin Island Sea Lab.

Website: <https://www.bco-dmo.org/dataset/875501>

Data Type: experimental

Version: 1

Version Date: 2022-06-15

Project

» [CAREER: Mechanisms of bioturbation and ecosystem engineering by benthic infauna](#) (Bioturbation and Ecosystem Engineering)

Contributors	Affiliation	Role
Dorgan, Kelly	Dauphin Island Sea Lab (DISL)	Principal Investigator
Clemo, William Cyrus	Dauphin Island Sea Lab (DISL)	Contact
Heyl, Taylor	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager
Rauch, Shannon	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager

Abstract

This dataset represents the acoustic properties of sediments collected from the Northern Gulf of Mexico, off the Alabama coast at 10 meters depth, following laboratory resuspension at the Dauphin Island Sea Lab.

Table of Contents

- [Coverage](#)
- [Dataset Description](#)
 - [Methods & Sampling](#)
 - [Data Processing Description](#)
- [Related Publications](#)
- [Related Datasets](#)
- [Parameters](#)
- [Instruments](#)
- [Project Information](#)
- [Funding](#)

Coverage

Spatial Extent: Lat:30.2222 Lon:-88.1391

Temporal Extent: 2020-01-29 - 2020-02-27

Methods & Sampling

We resuspended the surface 5 cm of natural muddy sediment cores in the lab and compared temporal changes in sediment compaction to changes in surface and subsurface cohesion over 30 days post resuspension. Sediment-water interface (SWI) height and acoustic sound speed through sediment, which depends on bulk density, provided continuous and nondestructive metrics of compaction, and sediment porosity and grain size were measured destructively to characterize sediment physical structure. We determined surface cohesion by measuring both eroded mass and turbidity resulting from increasing shear stress. Subsurface cohesion was determined from the force required for sediments to fail in tension. We compared surface and subsurface exopolymeric substance (EPS) concentrations to surface and subsurface cohesion measurements. We differentiated between water-soluble (colloidal) and sediment-bound EPS as we expected bound EPS to contribute more to sediment-organic matrix development and thus cohesion because they are directly bound to sediment grains rather than dissolved in porewater.

These data include the repeated acoustic measurements on the cores processed on day 30 from this experiment. A summary of data collected on cores processed over time points 0 days (no resuspension), then 1, 2, 3, 7, 14, and 30 days post resuspension is given in dataset 1. Detailed data on erosion measurements, as well as repeated non-destructive measurements of sediment-water interface height on cores processed on day 30 are provided in separate datasets.

We performed acoustic measurements following methods from Dorgan et al. (2020). Within a seawater tank, a 400 kHz three-cycle sinusoidal tone burst was transmitted horizontally through sediment cores to a receiver at 3 depths below the sediment surface (2.5, 5, 10 cm) (see Fig. 1 in Dorgan et al., 2020). To account for sound speed differences due to temporal variability in temperature and salinity, sound speed through sediment was normalized by the sound speed in seawater to obtain sound speed ratio (SSR). Each day, we also performed acoustic measurements on cores filled with seawater and with no core present. Sound speed in seawater and the lag time between the transmitted and received signals (time of flight) through sediment and seawater cores were used to calculate sound speed in sediment (v_p):

$$v_p = c_w / (1 - (c_w * \Delta t / d_s))$$

where c_w is sound speed in water, Δt is the difference in time of flight between seawater core (t_w) and sediment core (t_s), and d_s is the inner diameter of the core (Jackson and Richardson, 2007; Dorgan et al., 2020). SSR was then calculated by dividing v_p by c_w , where a higher SSR indicates more compact sediment.

Acoustics measurements done following Dorgan et al. 2020, JASA.

Data Processing Description

Data Processing:

Sound speed calculated from the lag between sent and received 3-pulse sine waves at 400 kHz using custom Matlab script. (see Dorgan et al. 2020 for details)

BCO-DMO Processing:

- Converted dates to format (YYYY-MM-DD)
- Adjusted field/parameter names to comply with BCO-DMO naming conventions
- Added a conventional header with dataset name, PI names, version date

[[table of contents](#) | [back to top](#)]

Related Publications

Clemo, W. C., Giles, K. D., & Dorgan, K. M. (2022). Biological influences on coastal muddy sediment structure following resuspension. *Limnology and Oceanography*. Portico. <https://doi.org/10.1002/lno.12213>
Results

Dorgan, K. M., Ballentine, W., Lockridge, G., Kiskaddon, E., Ballard, M. S., Lee, K. M., & Wilson, P. S. (2020). Impacts of simulated infaunal activities on acoustic wave propagation in marine sediments. *The Journal of the Acoustical Society of America*, 147(2), 812–823. <https://doi.org/10.1121/10.0000558>
Methods

[[table of contents](#) | [back to top](#)]

Related Datasets

IsRelatedTo

Dorgan, K., Clemo, W. Cyrus (2022) **Elevation of sediments collected from the Northern Gulf of Mexico following laboratory resuspension at the Dauphin Island Sea Lab**. Biological and Chemical Oceanography Data Management Office (BCO-DMO). (Version 1) Version Date 2022-06-15 <http://lod.bco-dmo.org/id/dataset/875514> [\[view at BCO-DMO\]](#)

Dorgan, K., Clemo, W. Cyrus (2022) **Elevation, erodibility, and acoustic properties of sediments**

collected from the Northern Gulf of Mexico following resuspension at the Dauphin Island Sea Lab in 2020. Biological and Chemical Oceanography Data Management Office (BCO-DMO). (Version 1) Version Date 2022-06-28 <http://lod.bco-dmo.org/id/dataset/875373> [[view at BCO-DMO](#)]

Dorgan, K., Clemo, W. Cyrus (2022) **Erodibility of sediments collected from the Northern Gulf of Mexico following laboratory resuspension at the Dauphin Island Sea Lab.** Biological and Chemical Oceanography Data Management Office (BCO-DMO). (Version 1) Version Date 2022-06-24 <http://lod.bco-dmo.org/id/dataset/875391> [[view at BCO-DMO](#)]

[[table of contents](#) | [back to top](#)]

Parameters

Parameter	Description	Units
coreID	named as "D_samplngday(max30)_replicate(A-E)"	unitless
latitude	latitude of sample site	decimal degrees
longitude	longitude of sample site (West is negative)	decimal degrees
waterdepth	water depth	meters (m)
date	Date in format YYYY-MM-DD	unitless
time_day	time of day	days
timepoint	time treatment (max 30)	unitless
replicate	1-4 corresponds with A-D in coreID	unitless
depth	depth in sediment core	centimeters (cm)
soundspeedratio_mean	ratio of sound speed in mud to sound speed in water	unitless

[[table of contents](#) | [back to top](#)]

Instruments

Dataset-specific Instrument Name	HP 33120 A function generator
Generic Instrument Name	Generator
Generic Instrument Description	A generator is an engine designed to produce electricity or a device designed to produce a vapor or gas.

Dataset-specific Instrument Name	Olympus immersion transducer
Generic Instrument Name	Immersion Transducer
Generic Instrument Description	An immersion transducer is a single element longitudinal wave transducer with a 1/4 wavelength layer acoustically matched to water. Immersion transducers are specifically designed to transmit ultrasound in applications where the test parts are partially or wholly immersed in water, which allows a uniform and fast coupling technique for rapid scanning of parts.

Dataset-specific Instrument Name	Krohn-Hite model 7500 Amplifier
Generic Instrument Name	Power Amplifier
Generic Instrument Description	An electronic device designed to take an input signal and output an increased signal strength.

[[table of contents](#) | [back to top](#)]

Project Information

CAREER: Mechanisms of bioturbation and ecosystem engineering by benthic infauna (Bioturbation and Ecosystem Engineering)

Coverage: Dauphin Island Sea Lab, Dauphin Island, AL

NSF abstract:

Marine sediments are important habitats for abundant and diverse communities of organisms that are important as food sources for higher trophic levels, including commercially important species. Through burrowing, constructing tubes, and feeding on sediments, these animals modify their physical and chemical environments to such an extent that they are considered ecosystem engineers. Bioturbation, the mixing of sediments by animals, is important in regenerating nutrients and transporting pollutants and carbon bound to mineral grains. Despite its importance, our ability to predict bioturbation rates and patterns from the community structure is poor, largely due to a lack of understanding of the mechanisms by which animals mix sediments. This project builds on earlier work showing that animals extend burrows through muddy sediments by fracture to test the hypothesis that the mechanical properties of sediments that affect burrowing mechanics also affect sediment mixing. More broadly, this project examines the relative contributions of (i) the functional roles of the organisms in the community, (ii) the mechanical properties of sediments, and (iii) factors that might increase or decrease animal activity such as temperature and food availability to bioturbation rates. Burrowing animals modify the physical properties of sediments, and this project quantifies these changes and tests the hypothesis that these changes are ecologically important and affect community succession following a disturbance. In addition to this scientific broader impact, this project involves development of instrumentation to measure sediment properties and includes a substantial education plan to introduce graduate, undergraduate, and middle school students to the important role that technology plays in marine science.

Through burrowing and feeding activities, benthic infauna mix sediments and modify their physical environments. Bioturbation gates the burial of organic matter, enhances nutrient regeneration, and smears the paleontological and stratigraphic record. However, current understanding of the mechanisms by which infaunal activities mix sediments is insufficient to predict the impacts of changes in infaunal community structure on important sediment ecosystem functions driven by bioturbation. This project tests specific hypotheses relating infaunal communities, bioturbation, and geotechnical properties with the ultimate goal of understanding the dynamic changes and potential feedbacks between infauna and their physical environments. This project integrates field and lab experiments to assess the relative importance of infaunal community structure and activities to bioturbation rates. Additionally, this project builds on recent work showing that muddy sediments are elastic gels through which worms extend burrows by fracture to propose that geotechnical properties of sediments mediate bioturbation by governing the release of particles from the sediment matrix during burrow extension. Finite element modeling determines how the release of particles by fracture during burrowing depends on the fracture toughness (cohesion) and stiffness (compaction) of sediments and complements laboratory experiments characterizing the impact of geotechnical properties on burrowing behaviors. The proposed research also aims to determine whether impacts of infauna on geotechnical properties are ecologically important. Changes in infaunal communities and geotechnical properties following an experimental physical disturbance address the hypothesis that ecosystem engineering of bulk sediment properties facilitates succession.

This award reflects NSF's statutory mission and has been deemed worthy of support through evaluation using the Foundation's intellectual merit and broader impacts review criteria.

[[table of contents](#) | [back to top](#)]

Funding

Funding Source	Award
NSF Division of Ocean Sciences (NSF OCE)	OCE-1844910

[[table of contents](#) | [back to top](#)]